

EM converterLED BASIC

Features

Emergency driver

- Model:FAT-LED-F1 B
- Power for:5-20W
- Input voltage:AC85-265V,output:DC230V
- Material:ABS+Aluminum
- Size:255*40*25mm
- Battery:li-ion 18650 11.1 V 2600mAH
- Emergency power:5-20W
- Emergency time:90min
- Certificate: CE Rohs
- Application: 5-20W LED light ,LED Tube

Properties

- Non maintained operation
- Emergency time:90min
- Operating time selectable with plug (duration link)
- Compatible with all dimmable and non-dimmable constant current LED Driver
- 3-pole technology: 2-pole LED module changeover and delayed power switching for the LED Driver
- Automatic shutdown of output if LED load is out of range
- Constant power output
- Maximum light output for all LED modules
- Electronic charge system
- Deep discharge protection
- Short-circuit-proof battery connection
- Polarity reversal protection for battery provided by 3-pole connector
- Automatic detection of the connected battery technology
NiMH or LiFePO4 batteries

Batteries

- High-temperature cells
- LA or 18650 cells
- 4-year design life for NiMH batteries
- 1-year guarantee for NiMH batteries
- 2 – 4 years design life for batteries
- 2-year guarantee for LiFePO4 batteries

