PHILIPS Lighting



SmartBright Highbay

BY239P LED180/NW PSU GM G2

Lens

SmartBright Highbay is a high efficient and reliable LED luminaire. Designed as the point to point replacement for HPI 250 W/400 W luminaires, it offers customers all the benefits of LED lighting – reduced energy consumption, longer service time and less maintenance. In addition, with the high quality of the optical cover, it provides an excellent quality of light, which effectively improves the comfort of your environment.

Product data

General information	
General information	
Light source colour	840 neutral white
Optical cover/lens type	Lens
Control interface	-
Protection class IEC	Safety class I (I)
Flammability mark	NO [-]
CE mark	CE mark
Number of products on MCB (16 A type B)	6
Light source engine type	LED
Operating and electrical	
Input Voltage	220 to 240 V
Input frequency	50 or 60 Hz
Inrush current	42 A
Power factor (min.)	0.95
Controls and dimming	
Dimmable	No

Mechanical and housing	
Housing material	Aluminum die–cast
Optical cover/lens material	Polycarbonate
Optical cover/lens finish	Clear
Overall height	93 mm
Overall diameter	319 mm
Effective projected area	0.06 m²
Colour	Dark gray
Dimensions (height x width x depth)	93 x NaN x NaN mm
Approval and application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Insulation Coverage Rating	Partial coverage acc. to IEC 60598-18.1
Initial performance (IEC compliant)	
Initial luminous flux (system flux)	19500 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	130 lm/W

SmartBright Highbay

Init. Corr. Colour Temperature	4000 K
Init. Colour rendering index	>80
Initial chromaticity	(0.385, 0.380) SDCM<5
Initial input power	150 W
Power consumption tolerance	+/-10%
Application conditions	
Ambient temperature range	-20 to +45 ℃
Product data	
Full product code	871951454105400

Order product name	BY239P LED180/NW PSU GM G2
EAN/UPC – product	8719514541054
Order code	54105400
SAP numerator - quantity per pack	1
Numerator – packs per outer box	1
SAP material	911401640407
Net Weight (Piece)	1.840 kg



Dimensional drawing



BY239P LED180/NW PSU GM G2



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, March 16 - data subject to change