## seeral



## **SPECIFICATION SHEET**

**Product Code** 

CPC035++

**Product Description** 

13A 1 Gang DP Switched UK Socket



eneral Information	
Dimensions	86mm x 86mm x 27.5mm
Finishes Available	CPC035: White, CPC035SV: Silver (RAL 9006 (White Aluminium))
Material Composition	Front Plate: Polycarbonate
	Insert, Switch & Base: Polycarbonate
	Terminals: Brass Plated Steel
	Terminal Screws: Steel and Yellow Passivated
	Internal Busbars: Formed Pressed Brass
	Silver "On-lay" Copper/Brass Contacts
Maximum Voltage	250V~ 50Hz
Current Rating	13A
Fixing Centres	60.3mm
Terminal Screw Size	4mmø
Terminal Torque	1.2Nm
Terminal Capacity	3 x 2.5mm², 2 x 4mm², 1 x 6mm²
Switched	Yes
Double Pole	Yes
Back Box Depth	35mm Minimum
Temperature Rating	-5° to +40°C
Warranty	10 Years (Domestic)

Standards	BS 1363-2: 2016
Additional Information	Ensure that the mains supply is isolated before commencing installation. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Errors & Omissions excluded. Specification is subject to change without notice.

**Scolmore International Limited** 1 Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB. Page 1 of 1 Rev.1.1

e sales@scolmore.com t 01827 63454 w www.scolmore.com f 01827 63362