

Technical Specification



Insert, Switch & Base: Polycarbonate

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Product Code: CPC036BK Description: 13A 2 Gang Double Pole Switched UK Socket



General Information

Product Dimensions 146mm (W) x 86mm (H) x 27.5mm (D)
Plate Dimensions 146mm (W) x 86mm (H) x 6.5mm (D)

Insert Black
Plate Finish Black

Materials Cover Plate: Polycarbonate
Terminals: Brass Plated Steel

Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Maximum Voltage 250V∼ 50Hz

Load Rating 13A
Plate Fixing Centres 120.6mm
Terminal Size 4mmø
Terminal Torque 1.2Nm

Terminal Capacity 3 x 2.5mm² or 2 x 4mm²

Double Pole Yes
Ingress Protection IP20

Back Box Depth 35mm Minimum

Termination Type Screw

Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS 1363-2: 2016 +A1: 2018

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.