

Product Code: CPC215BK

Description: 45A 3 Termination Plate With Optional Cable Outlet



**General Information**

<b>Product Dimensions</b>	86mm (W) x 86mm (H) x 24mm (D)	
<b>Plate Dimensions</b>	86mm (W) x 86mm (H) x 6.5mm (D)	
<b>Insert</b>	Black	
<b>Plate Finish</b>	Black	
<b>Materials</b>	Cover Plate: Polycarbonate Terminals: Brass Earth Strap: Mild Steel	Insert & Base: Polycarbonate Terminal Screws: Steel & Yellow Passivated
<b>Maximum Voltage</b>	250V~ 50Hz	
<b>Load Rating</b>	45A	
<b>Plate Fixing Centres</b>	60.3mm	
<b>Terminal Size</b>	8mmø	
<b>Terminal Torque</b>	2.5Nm	
<b>Terminal Capacity</b>	2 x 10mm <sup>2</sup> Max.	
<b>Flex Outlet</b>		
<b>Ingress Protection</b>	IP20	
<b>Back Box Depth</b>	35mm Minimum	
<b>Termination Type</b>	Screw	
<b>Cable Restraint Provided</b>	18mmø	
<b>Operational Temperature</b>	-5°C to +40°C	
<b>Warranty</b>	10 Years	
<b>Standards</b>	BS 5733: 2010	

**Additional Information**

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.