

Technical Specification

Product Code: CPC771BK

Description: 13A 1 Gang Switched UK Socket With USB Outlet



General Information		
Product Dimensions	86mm (W) x 86mm (H) x 38.5mm (D)	
Plate Dimensions	86mm (W) x 86mm (H) x 6.5mm (D)	
Insert	Black	
Plate Finish	Black	
Materials	Cover Plate: Polycarbonate Terminals: Brass Contacts: Silver "on-lay" Copper / Brass PCB: Electronic Components	Insert, Switch & Base: Polycarbonate Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
Maximum Voltage	250V~ 50Hz	
Load Rating	13A	
Plate Fixing Centres	60.3mm	
Terminal Size	4mmø	
Terminal Torque	1.2Nm	
Terminal Capacity	3 x 2.5mm ² or 2 x 4mm ²	
Single Pole	Yes	
Twin Earth Terminals	Yes	
USB Charging Output Total	5V DC, 2.1A	
Number Of USB Outputs	1	
USB Type	USB Type "A"	
USB Standby Current	2mA	
Product Markings	USB 5V 2.1A	
Ingress Protection	IP20	
Back Box Depth	35mm Minimum	
Termination Type	Screw	
Operational Temperature	-5°C to +40°C	
Warranty	10 Years, 1 Year Electronics	
Standards	BS 1363-2: 2016 +A1: 2018 BS EN 62368-1: 2014, BS EN 62680-1-1: 2015	
Additional Information	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.	

CE

Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 **E:** sales@scolmore.com | **W:** scolmore.com

Page 1 of 1 Rev.1.0 Errors & Omissions excluded. Specification is subject to change without notice.