

## **Technical Specification**



Insert, Switch & Base: Polycarbonate

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Product Code: CPC811BK Description: 10AX Single Pole 1 Gang 2 Way Plate Switch



## **General Information**

Product Dimensions 86mm (W) x 86mm (H) x 31.5mm (D) 86mm (W) x 86mm (H) x 6.5mm (D)

Insert Black
Plate Finish Black

Materials Cover Plate: Polycarbonate

Terminals: Brass

Contacts: Silver "on-lay" Copper / Brass

Maximum Voltage 250V∼ 50Hz

Load Rating 10AX (Suitable For Inductive Loads)

Plate Fixing Centres 60.3mm
Terminal Size 3mmø
Terminal Torque 0.4Nm

**Terminal Capacity** 2 x 1.5mm<sup>2</sup> or 1 x 2.5mm<sup>2</sup>

Single Pole Yes Ingress Protection IP20

Back Box Depth 35mm Minimum

Termination Type Screw

Operational Temperature -5°C to +40°C

Warranty 10 Years

**Standards** BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com



