

## **Technical Specification**

Product Code: CPC814BK

Description: 10AX Single Pole 4 Gang 2 Way Plate Switch



General Information		
Product Dimensions	86mm (W) x 86mm (H) x 31.5mm (D)	
Plate Dimensions	86mm (W) x 86mm (H) x 6.5mm (D)	
Insert	Black	
Plate Finish	Black	
Materials	Cover Plate: Polycarbonate	Insert, Switch & Base: Polycarbonate
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass
Maximum Voltage	250V~ 50Hz	
Load Rating	10AX (Suitable For Inductive Loads)	
Plate Fixing Centres	60.3mm	
Terminal Size	3mmø	
Terminal Torque	0.4Nm	
Terminal Capacity	2 x 1.5mm <sup>2</sup> or 1 x 2.5mm <sup>2</sup>	
Two Way	Yes	
Ingress Protection	IP20	
Back Box Depth	35mm Minimum	
Termination Type	Screw	
Operational Temperature	-5°C to +40°C	
Warranty	10 Years	
Standards	BS EN 60669-1:1999 +A1:2002 +A2:2008	
Additional Information	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.	

CE