

SPECIFICATION SHEET

Product Code

CPC814++

Product Description

10AX SP 4 Gang 2 Way Plate Switch


General Information

Dimensions	86mm x 86mm x 31.5mm
Finishes Available	CPC814: White, CPC814SV: Silver (RAL 9006 (White Aluminium))
Material Composition	Front Plate: Polycarbonate Insert, Switch & Base: Polycarbonate Terminals: Brass Plated Steel Terminal Screws: Steel and Yellow Passivated Internal Busbars: Formed Pressed Brass Silver "On-lay" Copper/Brass Contacts
Maximum Voltage	250V~ 50Hz
Current Rating	10AX (Suitable For Inductive Loads)
Fixing Centres	60.3mm
Terminal Screw Size	3mm \emptyset
Terminal Torque	0.8Nm
Terminal Capacity	2 x 4mm ² Max.
Switched	Yes
Two Way	Yes
Back Box Depth	35mm Minimum
Temperature Rating	-5° to +40°C
Warranty	10 Years (Domestic)

Standards

BS EN 60669- 1: 1999 + A1: 2002 + A2: 2008

Additional Information

Ensure that the mains supply is isolated before commencing installation. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.