

SPECIFICATION SHEET

Product Code CPC822N++

Product Description 20A DP 1 Gang Plate Switch With Neon



General Information

| | |
|----------------------|--|
| Dimensions | 86mm x 86mm x 31.5mm |
| Finishes Available | CPC822N: White, CPC822NSV: Silver (RAL 9006 (White Aluminium)) |
| Material Composition | Front Plate & Neon Lens: Polycarbonate Insert, Switch & Base: Polycarbonate Terminals: Brass Plated Steel Terminal Screws: Steel and Yellow Passivated Internal Busbars: Formed Pressed Brass Silver "On-lay" Copper/Brass Contacts |
| Maximum Voltage | 250V~ 50Hz |
| Current Rating | 20A |
| Fixing Centres | 60.3mm |
| Terminal Screw Size | 3mm \emptyset |
| Terminal Torque | 0.8Nm |
| Terminal Capacity | 2 x 4mm ² Max. |
| Switched | Yes |
| Double Pole | No |
| Twin Earth | Yes |
| Back Box Depth | 35mm Minimum |
| Temperature Rating | -5° to +40°C |
| Warranty | 10 Years (Domestic) |

Standards

BS EN 60669- 1: 1999 + A1: 2002 + A2: 2008

Additional Information

Ensure that the mains supply is isolated before commencing installation. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.